

Straight Pattern Snips

74410~74416

- Drop forged of finest quality steel induction hardened edges 60HRC
- Cuts straight flat face guides tool along straight line
- Blades individually hand edged for maximum cutting efficiency
- Cushion handle for comfort and better grip



74410 ~ 74416

KT NO.	Overall length mm	Cutting length mm	Copper (soft)	Cutting capacities (mm)			Stainless steel304	Scales	Box / Carton
				Cold-rolled Steel (soft)	Hard steel HRC 30 (Hard)				
74410	254	51	0.94	0.78	0.60	0.45	480	6 / 36	
74412	305	70	1.15	0.91	0.70	0.63	650	6 / 24	
74414	356	76	1.41	1.20	1.00	0.70	780	6 / 24	
74416	415	63	2.00	1.60	1.20	1.00	1700	3 / 12	

Curved Tin Snips

74512

- Drop forged of finest quality steel induction hardened edges 60HRC
- Double curved, hollow ground blades reduce friction for easier cutting
- British Gilbow type
- Cushion handle for comfort and better grip

74514



74512 / 74514

KT NO.	Overall length mm	Cutting length mm	Copper (soft)	Cutting capacities (mm)			Stainless steel304	Scales	Box / Carton
				Cold-rolled steel (soft)	Hard steel HRC 30 (Hard)				
74512	305	60	1.15	0.91	0.70	0.63	670	6 / 24	
74514	356	65	1.40	1.20	100	0.70	920	6 / 24	

Duckbill Pattern Snips

74613

- Drop forged of finest quality steel induction hardened edges 60HRC
- Cuts moderately tight curves left, right or straight in light stock
- Blades individually hand edged for maximum cutting efficiency
- Cushion handle for comfort and better grip



KT NO.	Overall length mm	Cutting length mm	Copper (soft)	Cutting capacities (mm)			Stainless steel304	Scales	Box / Carton
				Cold-rolled steel (soft)	Hard steel HRC 30 (Hard)				
74613	330	72	1.20	0.84	0.61	0.61	720	6 / 24	

Saw

7911-12

- Sliding metal bow
- Lightweight, resistant to oxidization and oil
- Two blade positions 45° and 90° including flush cut
- Ergonomic handle with hand stop
- Handle material : Zinc frame, soft grip TPR handle



KT NO.	Adjustable blade length (mm)	Overall length mm	Scales	Box / Carton
7911-12	305	400	628	6 / 36
7911-12P01	Blade			100 / 1200

